



The PT33LSC is the world's first fully automated laminator that slits and cuts to finished size saving hours of trimming and cutting after the laminating process. Designed to meet the demands of the digital short run printer, the PT33LSC not only cuts to bleed but has pouch mode where you can choose your encapsulation size or perform true single sided laminating with the ability to easily control the curl with the anti-curl devise. Automatic setup, productive speeds and the efficient pile feeder makes for a "set it and forget it" laminating experience.

SPECIFICATIONS

Min Sheet Size	7" x 7"
Max Sheet Size	13" x 19.7"
Paper Thickness	100 – 350 GSM
Lamination Thickness	1.5, 3, 5 mil
Laminating Modes	Double sided, single sided with anti-curl device with no need for release film, adjustable encapsulation and trim to bleed
Lamination Width	4.4" - 12.9" *custom widths available
Cutting Method	2 automatic setup side slitters and 1 guillotine cutter assembly
Feeding Method	2" vacuum pile feeder
Speed	Variable speeds up to 10 feet per minute
Power Requirements	110-130V, 50/60Hz, 15A

While every effort was made at time of publication to ensure accuracy, Graphic Whizard will not be liable for omissions or errors. Specifications and information are subject to change without notice. Actual results are dependent upon application. Paper stock, print engine used and environmental conditions will affect results. 08/17