

GW 460ATS EVA

This perfect binding system is easy to use and provides consistent, professional quality products for short to medium run solutions. With a durable build and features included standard that are normally found on more expensive units, the 460A is an affordable and efficient solution for your perfect binding needs.



Efficient
Strong
Durable

Product Features:

- Clamp Opens and closes with the single press of a button
- Notching blades are housed beneath safety covers to ensure operator safety
- Hot melt glue is applied to the spine and side by a rotating applicator drum by
- A scraper bar ensures that a smooth and uniform thickness of glue is always applied
- Nip dwell time can be adjusted to ensure professional looking finished pieces are produced every time

Electrical:	220-240V 1phase / 20A
Cycle Speed:	450 cycles/hour
Max Binding Length:	18.1"(46cm)
Max Binding Thickness:	2.25"(6cm)
Notching:	Double layer (24 blades)
Dimensions:	Length: 62" (156 cm)
	Width: 29" (72 cm)
	Height: 51" (130 cm)
	Weight: 575 lbs (260 kg)

Clamping of Sheets:	Electric / fully automatic
Clamping of Cover:	Electric
Side Gluing:	Yes, applicator drums
Cover Insertion:	Manual
Warm up Time:	20- minutes approx.
Display:	Color Touchscreen
Dust Extraction:	Vacuum, enclosed



GRAPHIC WHIZARD AUTHORIZED DEALER:

WWW.GRAPHICWHIZARD.COM