graphic whizard
print finishing solutions

PT 33LSC CR

LAMINATE • SLIT • CUT • CORNER ROUND

First of its kind for the digital short run printer. The PT 33LSC CR not only cuts to bleed for a finished product, but also offers a variable size encapsulation mode with corner rounding. Choose your encapsulation width through the programming for 2-sided pouch lamination with a customizable border size and corner rounding. Alternatively, you can flush cut to bleed with or without inline automatic corner rounding.

The PT 33LSC CR boasts the highest film yield in operation with only a 1/8" gap between sheets. Automatic set-up, productive speeds, and the efficient 2" vacuum pile feeder make for a 'set it and forget it' laminating experience.

FEATURES

- Slits and cuts to finished size
- Film choices of gloss, matte, soft-touch and more!
- Pouch mode with a variable encapsulation size
- Automatic setup and program memory
- 2" vacuum pile feeder
- Inline corner rounding
- Variable speeds

SPECIFICATIONS

Minimum Sheet Size	7" x 7" (17.78 cm x 17.78 cm)
Maximum Sheet Size	13" x 19.7" (33.02 cm x 50.038 cm)
Paper Thickness	100-350 gsm
Lamination Thickness	1.5, 3 & 5 mil*
Lamination Width	4.4" – 12.9" (11.176 cm – 32.766 cm)* custom widths available
Laminating Modes	Double-sided encapsulation or trim to bleed
Cutting Method	2 automatic set-up side slitters and 1 guillotine cutter assembly
Corner Rounding	5 mm radius
Speed	Variable speeds up to 10 feet per minute
Feeding Method	2" (5.08 cm) vacuum pile feeder
Floor Model	Yes
Machine Weight	595lbs (270kg)
Machine Dimensions	64.9" x 24.4" x 43.3" (165cm x 62cm x110cm)
Electrical	110-130V, 60Hz 15A

NOTE: Machine performance will vary based on stock weight, type, and specifications of the job being performed.
WARRANTY: 1 year warranty (excludes consumables)

CONTACT US TODAY!
sales@graphicwhizard.com

GW-PT33LSCCR-SS-112024